

## NCK-TM4END-3W6S

### 3.0MP WIFI KIT END Series

#### Feature:

- Support DWDR, 3D DNR;;
- Day/Night(Auto ICR);
- IR range: 2 infrared lamps, 1 white lamps 20m-30m;
- H.265A/H.265+(compatible H.265/H.264) high profile, 8Ch WIFI NVR;
- Wi-Fi 6,support IEEE 802.11.AX,IEEE802.11b/g/n,Dual antenna,2.412~2.484GHz;
- Support video preview , recording, playback, backup;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari) , Support ARSP;
- Support WEB, CMS, VMS, JFEYE Platform;



#### Parameters:

	Model	NVR8008TM-UW6S
System	processor	Mstar
	system	Embedded Linux
Video	Video input	8ch 5M
	Playback	8ch 5M
	Decode	H.265A/H.265+(compatible H.265/H.264)
Audio	Compression	G.711a
	Intercom	support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel/Face
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
WIFI	Bands	2.412~2.484GHz
	Standard	IEEE 802.11.AX compatible with 802.11b/g/n
Interface	HDMI output	1*HDMI
	VGA output	1*VGA
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port,8*Wi-Fi
	POE ports	N/A
	Audio I/O	1/1(3.5mm)
	Alarm I/O	0/0

	USB Port	2*USB2.0 ports
	HDD	1*SATA interface (Up to 14TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W (Without HDD)
	Weight	Around 1KG
	Dimension	255(L)* 236mm(W)* 44mm(H)

Camera	<b>Medol</b>	<b>IPC-END8330PX-IR2R-W6S</b>
	sensor	4.0 million 1/3" CMOS sensor
	Min. illumination	Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
	Shutter time	1/50(1/60)s to 1/10,000 s
	Lens	HD lens 3.11mm @F2.2
	Lens mount	M12
	Day&night	IR cut filter with auto switch
Image	Max.image reolution	2304*1296
	Frame rate	PAL: 2304*1296@12fps, 1920*1080@12fps NTSC: 2304*1296@12fps, 1920*1080@12fps
	setting	Saturation, brightness and contrast are adjustable through IE browser or client software.
Compression	Video compression	H.265A1/H.265+(compatible H.265/H.264) HighProfile, JPEG snapshot
	Bite rate	0.1Mbps~8Mbps
	Audio compression	G.711a
Network	Storage	Network storage
	Alarm	Face detection,human detect, Motion detection, video loss, video block, etc.
	protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, (HTTPS, SIP, 802.1x, IPv6 option )
	Features	anti-flicker, dual-stream, heartbeat, password protection
Interface	Ethernet	wifi transfer, support direct connection by wps
	Audio I/O	1/0 (RCA)
General	temperature	-10°C- + 60°C
	humidity	10%-90% RH
	Power supply	DC12V±10%
	IR range	2 infrared lamps, 1 white lamps "IR2" :20-30 meters
	Consumption	MAX 4W
	Ingress Protection	IP66
	Weight	Around 300g
	Dimension	176mm*66mm*62mm