

4MP PoE

Dual-light Bullet IP Camera ES Series

IPC-ES8340PN-IR2R-PAT




Introduction

IPC-ES8340PN-IR2R-PAT is a waterproof bullet network camera, suitable for places with low or no light conditions and high definition image quality, such as roads, warehouses, underground parking lots, bars, pipelines, parks, etc.



Dimension



Main Features



HD Lens



PoE



Multi-Platform Support



IP67 Waterproof



Human detection



Onvif



Automatic electronic shutter



Automatic ICR



Face Detection



Mobile Monitoring



Voice intercoms



Double light alert

Product Parameters

Model IPC-ES8340PN-IR2R-PAT

Camera

Sensor	1/3" low illumination CMOS sensor
illumination	Color:0.01Lux @(F1.2,AGC ON);0 Lux with IR B/W:0.001 Lux @(F1.2,AGC ON);0 Lux with IR
Shutter	1/50(1/60)s to 1/10,000s
Lens	HD lens 4/6mm(optional)
Lens Mount	M12
Day&Night	IR cut filter with auto switch

Image

Max resolution	2560*1440
Frame Rate	2560*1440@25fps,2304*1296@25fps, 1920*1080@25fps
Setting	Saturation, brightness and contrast are adjustable through IE browser or client software.

Compression

Video Encoding	H.265AI(compatible H.265/H.264) HighProfile, JPEG snapshot
Bite Rate	0.1Mbps~8Mbps
Audio Encoding	G.711a

Network

Storage	Network storage
Alarm	Face detection , human detection, Motion detection, video loss, video block, etc.
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, (HTTPS, SIP, 802.1x, IPv6 option
Features	anti-flicker, dual-stream, heartbeat, password protection

General

Temperature	-10°C- + 60°C
Humidity	10%-90% RH
Power	DC12V±10%/POE
IR Range	4* (Infrared + white light) "IR2":20-30 meters
Consumption	MAX 4W
Material	metal
waterproof	IP67
Weight	Around 360g
Dimension	68.36mm*68.36mm *174.29mm

Interface

Ethernet	1*10/100Mbps Ethernet port, RJ45 port
Audio I/O	1/1 (Built-in mic/speaker)