

ATC-35V2B2-W5 3.6mm (5MP)

Features:

5MP HD Analog Output (AHD / TVI / CVI / CVBS)

1/2.8" High-Performance Progressive Scan COMS

Support 3.6mm Lens

Support DNR / DWDR

Support Low Illumination, Warm Light Day Night Full Colour

Support ICR Switch, Realize Day & Night Monitor

Support OSD Menu / DIP Switch / Circulation Button Switch (Optional)

Applicable to the Financial Departments, Telecommunications, Government, Schools, Airport, Factory, Hotels, Museum, Public Transportation and Other Places



Model	ATC-35V2B2-W5
Spec	5MP 4 in 1 Camera Module
Detailed Spec	
Sensor	1/2.8" IMX335
DSP	FH8538M
System	PAL / NTSC
Effective Pixel	2560(H) x 1920(V) 5MP 4:3 2560 (H) x 1440 (V) 4MP 16:9
Illumination	0.01 Lux @ (F1.2, AGC On), 0 Lux With IR
Shutter	Auto
D/N	EXT (Default) / Color / BW
Synchronously	Internal
FPS	5MP@20fps / 12.5fps / 4MP@25fps / 30fps / 15fps
Video Output	AHD / TVI / CVI / Can be Switch
OSD Menu	
Exposure	Shutter / AGC / Brightness

AWB	ATW / MWB
Day-Night	Infrared / Color / B&W
Video Setting	Contrast / Sharpness / Color Gain / DNR
Video Output	AHD : 5MP20 / 12.5 / 4MP25 / 30 /15 CVBS: PAL/NTSC TVI: 5MP20 / 12.5 / 4MP25 / 30 /15 CVI: 4MP25 /30
Language	Chinese / English
Common Spec	
Operation Temperature	(-20° C to 60° C)
Working Humidity	Relative Humidity Less Than 90%
Power	DC12V (+20%) - 70MA
Size	32*32/38*38 (mm)

