

## ADVR8004A-NGS-V2

### 1 SATA H.265 4ch Analog HD DVR A Series

#### Features:

- Support 4ch 5M unreal-time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1SATA(Up to 14TB);
- 1\*10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control
- Support human detection, face detection and other intelligence

#### Model:

ADVR8004A-NGS-V2

#### Interface:



#### Parameters:



	Model	ADVR8004A-NGS-V2	
System	processor	NT98321	
Video	Codec	H.265+/H.265/H.264	
	Preview	4ch5M@12fps(6 in 1)/4ch4M@15fps(6 in 1)/4ch3M@18fps(6 in 1)/4ch1080P(6 in 1) default: 5M	
	Encode	4ch5M@12fps(6 in 1)/ 4ch4M@15fps(6 in 1)/4ch3M@18fps(6 in 1)/4ch1080P (6 in 1) default: 5M	
	Decode	1ch5M@12fps(6 in 1)/ 1ch4M@15fps(6 in 1)/1ch3M@18fps(6 in 1)/1ch1080P default: 5M	
	Multi-mode	Analog:	4ch 5M
		hybrid:	4*5M (analog) +4*5M (network)
	IP:	16ch 1080P/8ch 5M	
Playback		4/2/1ch	
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record mode	Manual>Alarm>Motion detection>Timing	
	Inquire mode	Inquire by Time/Calendar/Event/Channel	
	Storage mode	HDD Storage, Network Storage	
	Backup	Network, USB, SATA	
Interface	Video input	4*BNC(Support Coaxitron)	
	HDMI output	1*HDMI (MAX:4K)	
	VGA output	1*VGA (MAX:1080P)	
	Audio I/O	1/1	
	Alarm I/O	0/0	
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port	
	PTZ control	Support for multiple PTZ protocol	
	USB Port	2*USB2.0 ports	
	HDD	1*SATA interface (Up to14TB)	
General	Temperature	0 °C - + 55 °C	
	Humidity	10% -90% RH	
	Power supply	12V/2A	
	Consumption	<10W(Without HDD)	
	Weight	Around1KG	
	Dimension	255mm(L)* 215mm(W)* 44mm(H)	



**click here to  
watch VIDEO**