

NVR8032F-NKL-V3

H.265 4SATA NVR F Series



Features:

- 32ch4K video input;
- HDMI/VGA simultaneous video output;
- 1.5U Case, 4SATA(Up to 14TB);
- H.265AI/H.265+ (compatible H.265/H.264)
- 1*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- "Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc.;"
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS, MYEYE Platform;
- Support Multi-Lens;
- Support intelligent functions such as face detection, human shape detection, car shape detection, face video playback, car video playback.

Model:

NVR8032F-NKL-V3

Interface:



Parameters:

	Model	NVR8032F-NKL-V3
System	processor	NT98332
	system	Embedded Linux
Video	Video input	32ch4K
	Playback	4K(1+1)/5M(3+1)/4M(4+1)/3M(5+1)/1080P(8+2)
	Decode	H.265AI/H.265+ (compatible H.265/H.264)
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motiondetection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage, Cloud Storage
	Backup	Network, USB, SATA
Interface	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Ethernet port	1*RJ45 1*10/100/1000Mbps Ethernet port,
	POE ports	N/A
	Audio I/O	1/1
	Alarm I/O	16/4
	Serial Port	1*RS485,1*RS232
	USB Port	3*USB2.0 ports
General	HDD	4*SATA interface (Up to 14TB)
	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/6A
	Consumption	<10W (Without HDD)
	Weight	Around 1.6KG
	Dimension	440L)* 400.5mm(W)* 60mm(H)