

1080P BULLET IP CAMERA

R



Parameters:

Human Detect Spotlight

Features:

- HD picture quality: 2 million HD picture quality, clear and smooth image
- AI human detection: intelligent human detection, Effective filtering invalid alarm
- Personal voice ringtone: Custom personalized voice

ringtone, welcome guests anti-theft are appropriate

• Three night vision modes switched automatically: Double light alert, day and night full-color, infrared night vision and other modes can be freely switched

- Voice to talk: support two-way voice to talk,
- communication accessibility
- Storage management: support local TF card, maximum

support up to 128G, automatic loop coverage after full storage, Support cloud storage

- Connection mode: wired/wireless /AP connection
- Ingress Protection: IP66
- Mobile phone remote monitoring (iOS, Android)

Scenarios:

Apply for general family indoor and outdoor, villa, garage, shop, store and somewhere where require HD images but with dark light and poor sunshine.

Model:

EL-2D

Full color night vision; support two-way voice to talk; support local TF card		
Sensor200W 1/2.7 " Low illumination CMOS sensorMin.Color: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IRIllumination1/50(1/60)s to 1/10,000 sLensHD lens 3.6mm@F2.0 (Optional 6mm)LensM12Day&nightIR cut filter with auto switchEncoding formatII cut filter with auto switchVideoH.264+/H.265X High Profile, JPEG CaptureCoding rate0.1Mbps~8MbpsAudioG.711aImage1920*1080FPS1080P@6fpsConnection modes:wired /wireless/AP connectionPeaturesSupport three connection modes: wired /wireless/AP connectionPatteresIIIIon HD pictur= quality; AI human detection; Personal voice ringtone;Support cloud storage; IP66; Mobile phone remote monitoringOther-10°C~60°C, Humidity less than 90% (non-condensing) midityPower supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	Model	EL-2D
Min. IlluminationColor: 0.01Lux @(F1.2,AGC ON); 0 Lux with IR B/W: 0.001 Lux @(F1.2,AGC ON), 0 Lux with IR B/W: 0.001 Lux @(F1.2,AGC ON), 0 Lux with IRShutter time1/50(1/60)s to 1/10,000 sLensHD lens 3.6mm@F2.0 (Optional 6mm)LensM12Day&nightIR cut filter with auto switchEncoding formatIR cut filter with auto switchVideoH.264+/H.265X High Profile, JPEG CaptureCoding rate0.1Mbps~8MbpsAudioG.711aImage1920*1080FPS1080P@6fpsConnection modes:wired /wireless/AP connectionNetworkSupport three connection modes:Features22 million HD picture quality; AI human detection; Personal voice ringtone; support cloud storage; IP66; Mobile phone remote monitoringOther-10°C~60°C, Humidity less than 90% (non-condensing) midityPower supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	Camera	
IlluminationB/W: 0.001 Lux @ (F1.2,AGC ON),0 Lux with IRShutter time1/50(1/60)s to 1/10,000 sLensHD lens 3.6mm@F2.0 (Optional 6mm)Lens mountM12Day&nightIR cut filter with auto switchEncoding formatVideoVideoH.264+/H.265X High Profile, JPEG CaptureCoding rate0.1Mbps~8MbpsAudioG.711aImage1920*1080FPS1080P@6fpsConnection mode:Support three connection modes: wired /wireless/AP connectionNetworkSupport three connection modes: wired /wireless/AP connectionFeaturesSupport two-way voice to talk; support local TF cardSupport cloud storage; IP66; Mobile phone remote monitoringOtherTemperature/Hu midity-10°C~60°C, Humidity less than 90% (non-condensing)Power supplyDC12V±10%IR range10-30 metersConsumptionIP66WeightAbout 380g	Sensor	200W 1/2.7 " Low illumination CMOS sensor
LensHD lens 3.6mm@F2.0 (Optional 6mm)Lens mountM12Day&nightIR cut filter with auto switchEncoding formatIR cut filter with auto switchVideoH.264+/H.265X High Profile, JPEG CaptureCoding rate0.1Mbps~8MbpsAudioG.711aImageI020*1080FPS1080P@6fpsConnection modesupport three connection modes: wired /wireless/AP connectionNetworkSupport three connection modes: wired /wireless/AP connectionFeatures22 million HD picture quality; AI human detection; Personal voice ringtone; Ful color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoringOther-10°C~60°C, Humidity less than 90% (non-condensing) midityPower supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g		
Lens mount M12 Day&night IR cut filter with auto switch Encoding format IR cut filter with auto switch Video H.264+/H.265X High Profile, JPEG Capture Coding rate 0.1Mbps~8Mbps Audio G.711a Image 1920*1080 FPS 1080P@6fps Connection mode support three connection modes: wired /wireless/AP connection Network Support three connection modes: wired /wireless/AP connection Features support two-way voice to talk ; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight Mout 380g	Shutter time	1/50(1/60)s to 1/10,000 s
Day&night IR cut filter with auto switch Encoding format IR cut filter with auto switch Video H.264+/H.265X High Profile, JPEG Capture Coding rate 0.1Mbps~8Mbps Audio G.711a Image 1920*1080 FPS 1080P@6fps Connection mode connection Network Support three connection modes: wired /wireless/AP connection Features support three connection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other -10°C~60°C, Humidity less than 90% (non-condensing) midity Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Lens	HD lens 3.6mm@F2.0 (Optional 6mm)
Encoding formatVideoH.264+/H.265X High Profile, JPEG CaptureCoding rate0.1Mbps~8MbpsAudioG.711aImageImageMax Image size1920*1080FPS1080P@6fpsConnection modeSupport three connection modes: wired /wireless/AP connectionNetworkSupport three connection modes: wired /wireless/AP connectionFeatures22 million HD picture quality; AI human detection; Personal voice ringtone;Full color night vision; support two-way voice to talk; support local TF cardSupport cloud storage; IP66; Mobile phone remote monitoringOther-10°C~60°C, Humidity less than 90% (non-condensing)midityDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	Lens mount	M12
VideoH.264+/H.265X High Profile, JPEG CaptureCoding rate0.1Mbps~8MbpsAudioG.711aImageImageMax Image size1920*1080FPS1080P@6fpsConnection modeImageNetworkSupport three connection modes: wired /wireless/AP connectionFeaturesImage2 million HD picture quality; Al human detection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoringOtherImageTemperature/Hu midity-10°C~60°C, Humidity less than 90% (non-condensing)Power supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	Day&night	IR cut filter with auto switch
Coding rate0.1Mbps~8MbpsAudioG.711aImageG.711aImage1920*1080FPS1080P@6fpsConnection modeConnection modes: wired /wireless/AP connectionNetworkSupport three connection modes: wired /wireless/AP connectionFeatures22 million HD picture quality; AI human detection; Personal voice ringtone;Full color night vision; support two-way voice to talk; support local TF cardSupport cloud storage; IP66; Mobile phone remote monitoringOtherTemperature/Hu midity-10°C~60°C, Humidity less than 90% (non-condensing)Power supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	Encoding format	
AudioG.711aImageI920*1080Max Image size1920*1080FPS1080P@6fpsConnection modeSupport three connection modes: wired /wireless/AP connectionNetworkSupport three connection modes: wired /wireless/AP connectionFeaturesSupport three connection; Personal voice ringtone;2 million HD picture quality; AI human detection; Personal voice ringtone;Full color night visior; support two-way voice to talk; support local TF cardSupport cloud storae; IP66; Mobile phone remote monitoringOtherTemperature/Hu midity-10°C~60°C, Humidity less than 90% (non-condensing)Power supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	Video	H.264+/H.265X High Profile, JPEG Capture
Image Max Image size 1920*1080 FPS 1080P@6fps Connection mode Support three connection modes: wired /wireless/AP connection Network Support three connection modes: wired /wireless/AP connection Features 2 million HD picture quality; AI human detection; Personal voice ringtone; Full color night visior; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity D0°C~60°C, Humidity less than 90% (non-condensing) IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Coding rate	0.1Mbps~8Mbps
Max Image size1920*1080FPS1080P@6fpsConnection modeNetworkSupport three connection modes: wired /wireless/AP connectionFeaturesconnection2 million HD picture quality; AI human detection; Personal voice ringtone;Full color night vision; support two-way voice to talk; support local TF cardSupport cloud storage; IP66; Mobile phone remote monitoringOtherTemperature/Hu midity-10°C~60°C, Humidity less than 90% (non-condensing)Power supplyDC12V±10%IR range10-30 metersConsumptionIMAX 6WIngress ProtectionIP66WeightAbout 380g	Audio	G.711a
FPS 1080P@6fps Connection mode Support three connection modes: wired /wireless/AP connection Network Support three connection modes: wired /wireless/AP connection Features Image: Connection modes: wired /wireless/AP connection 2 million HD picture quality; AI human detection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Image	
Connection mode Network Support three connection modes: wired /wireless/AP connection Features 2 2 million HD picture quality; AI human detection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity -10°C~60°C, Humidity less than 90% (non-condensing) IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Max Image size	1920*1080
NetworkSupport three connection modes: wired /wireless/AP connectionFeatures2 million HD picture quality; AI human detection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoringOtherTemperature/Hu midity-10°C~60°C, Humidity less than 90% (non-condensing)Power supplyDC12V±10%IR range10-30 metersConsumptionMAX 6WIngress ProtectionIP66WeightAbout 380g	FPS	1080P@6fps
Network connection Features 2 2 million HD picture quality; AI human detection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Connection mode	
2 million HD picture quality; AI human detection; Personal voice ringtone; Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Network	
Full color night vision; support two-way voice to talk; support local TF card Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Features	
Support cloud storage; IP66; Mobile phone remote monitoring Other Temperature/Hu midity -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g	2 million HD picture quality; AI human detection; Personal voice ringtone;	
Other Temperature/Hu midity Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g		
Temperature/Hu -10°C~60°C, Humidity less than 90% (non-condensing) midity DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g		
midity -10°C~60°C, Humidity less than 90% (non-condensing) Power supply DC12V±10% IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g		
IR range 10-30 meters Consumption MAX 6W Ingress Protection IP66 Weight About 380g		-10 $^\circ C$ ~60 $^\circ C$, Humidity less than 90% (non-condensing)
Consumption MAX 6W Ingress Protection IP66 Weight About 380g	Power supply	DC12V±10%
Ingress Protection IP66 Weight About 380g	IR range	10-30 meters
Weight About 380g	Consumption	MAX 6W
	Ingress Protection	IP66
Dimension 182mm*66mm	Weight	About 380g
	Dimension	182mm*66mm

