

Save Master/user Password/name (0:0000,1:1111)	Armed/alarm delay sound ON(ON or OFF) Default
Remote/Sensor ID Register 10-93	Touch key-pad key tone ON(ON or OFF) Default
Armed/alarm Delay time 30(1-199)seconds Default	Working mode voice play ON(ON or OFF) Default
Hand-free time 5(1-199)seconds Default	Save alarm event name max:16 Default
Alarm sound mode ON(ON or OFF) Default	Timer to set working mode 2400:OFF Default
Alarm sound duration Set to 60(1-499)seconds 300 Sec	Set the working day 12345 Default
Erase remote/sensor ID code 10-93	Timer set working turn on/off OFF(ON or OFF) Default
Sensor loss supervision ON(ON or OFF) Default	IP/WiFi module working OFF(ON or OFF) Default
External siren power type AC(AC or Battery) Default	Save sensor name 20-89,92-93,98-99 max: 20
PIN CODE OFF (XXXX) GSM Use	Timer control power switch 2400-2400:OFF Default
Save dialer phone number (1-10)	GSM auto report SMS time 00:OFF(01-99)hours Default
Re-dialer times 3(1-6)times Default	AC power lost delay report time 30(00-99)minuteOFF00:OFF Set to 1min
Recording emergency message Default	INT Temperature level HI +16°C(-40-+60)°C Default
Voice re-play times 3(1-6)times Set to 1	INT Temperature level LO +4°C(-40-+60)°C Default
Digital dialer account Number 0000(0001-9999) CMS ID	EXT Temperature level HI +16°C(-40-+60)°C Default
Digital dialer data format Contact ID CMS USE	EXT Temperature level LO +4°C(-40-+60)°C Default
GSM MIC/SP signal level MIC:4SP:4 Default	Temperature level send SMS time 0:OFF(0-24)hours Default
Dialer mode PSTN(PSTN or GSM) Default	Temperature level HI turn off +12°C(0-40)°C Default
Ring back tone times OFF(0-9)times Default	Temperature level LO turn on +4°C(0-40)°C Default
Alarm event report mode Alarm(Alarm or all) Set to all	Save remote user name 10-19 : 1-3 Default
Tamper alarm to dialer ON(ON or OFF) Default	Setup sensor alarm function 20-89,92,93,98,99
Phone line lost to dialer ON(ON or OFF) Default	Working partition mode 1(1 or 2)partion Default
Keypad set quick Away/Home ON(ON or OFF) Default	Alarm console owner data max:64 Default

DISARM1-01
DISARM2-01
D/W OPEN:21 23
GSM 21:HI

- Save sensor name**
- (20):Tampered Switch
 - (21):Main Door
 - (22):Vibration
 - (23):Kitchen Door
 - (24):PIR
 - 25:
 - 26:

9:06 AM

FS-C DISARM1-01 DISARM2-01
POWER SWITCH- - #Anthony

9:06 AM

FRONTI # SENSOR TAMPER-24 #
Tampeted Switch

9:08 AM

FRONTI # PANIC-01 # Anthony

9:11 AM

FS-C DISARM1-10 DISARM2-01
POWER SWITCH- - #Anthony

9:11 AM

FRONTI # SENSOR TAMPER-24 #
Tampeted Switch