

Gigabit PoE Switch



4GE(PoE)+1GE(UP-LINK)+1SFP

- ★ Support IEEE802.3af/at/bt
- ★ 6KV lightning protection, 8KV Electro-Static, surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection
- ★ PoE Port: Port(1~4)*1000M
- ★ PoE++ Port: bt Port(4) 60W
- ★ UP-LINK: Port(Lan)*1000M, SFP*1000M
- ★ Bandwidth: 12Gbps, MAC address: 8K
- ★ AI Watchdog: Automatic detection, Automatic restart
- ★ Support 4core 12+/36-Power Supply & Support 8 core 1245+/3678-power supply
- ★ Power: 65W
- ★ Transmission Distance: 130m
- ★ Operating Temperature: -30°C~60°C
- ★ Storage Temperature: -40°C~70°C
- ★ Size: 187*139*43mm (L*W*H)
- Model: GNT-P1006GA



8GE(PoE)

- ★ Support IEEE802.3af/at/bt
- ★ 6KV lightning protection, 8KV Electro-Static, surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection
- ★ PoE Port: Port(1~8)*1000M
- ★ PoE++ Port: bt Port(7~8) 60W
- ★ UP-LINK: Port(1~8)*1000M
- ★ Bandwidth: 16Gbps, MAC address: 8K
- ★ AI Watchdog: Automatic detection, Automatic restart
- ★ Support 4core 12+/36-Power Supply & Support 8 core 1245+/3678-power supply
- ★ Power: 120W
- ★ Transmission Distance: 130m
- ★ Operating Temperature: -30°C~60°C
- ★ Storage Temperature: -40°C~70°C
- ★ Size: 187*139*43mm (L*W*H)
- Model: GNT-P1008G6



8GE(PoE)+2GE(UP-LINK)

- ★ Support IEEE802.3af/at/bt
- ★ 6KV lightning protection, 8KV Electro-Static, surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection
- ★ PoE Port: Port(1~8)*1000M
- ★ PoE++ Port: bt Port(7~8) 60W
- ★ UP-LINK: Port(L1~L2)*1000M,
- ★ Bandwidth: 20Gbps, MAC address: 8K
- ★ AI Watchdog: Automatic detection, Automatic restart
- ★ Support 4core 12+/36-Power Supply & Support 8 core 1245+/3678-power supply
- ★ Power: 120W
- ★ Transmission Distance: 130m
- ★ Operating Temperature: -30°C~60°C
- ★ Storage Temperature: -40°C~70°C
- ★ Size: 187*139*43mm (L*W*H)
- Model: GNT-P1210G7



8GE(PoE)+2GE(UP-LINK)+2SFP

- ★ Support IEEE802.3af/at/bt
- ★ 6KV lightning protection, 8KV Electro-Static, surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection
- ★ PoE Port: Port(1~8)*1000M
- ★ PoE++ Port: bt Port(7~8) 60W
- ★ UP-LINK: Port(L1~L2)*1000M, SFP(S1~S2)*1000M
- ★ SFP Port: SFP(S1~S2)*1000M
- ★ Bandwidth: 24Gbps, MAC address: 8K
- ★ AI Watchdog: Automatic detection, Automatic restart
- ★ Support 4core 12+/36-Power Supply & Support 8 core 1245+/3678-power supply
- ★ Power: 120W
- ★ Transmission Distance: 130m
- ★ Operating Temperature: -30°C~60°C
- ★ Storage Temperature: -40°C~70°C
- ★ Size: 187*139*43mm (L*W*H)
- Model: GNT-P1012G6



16GE(PoE)+2SFP

- ★ Support IEEE802.3af/at/bt
- ★ 6KV lightning protection, 8KV Electro-Static, surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection
- ★ PoE Port: Port(1~16)*1000M
- ★ PoE++ Port: bt Port(15~16) 60W
- ★ UP-LINK: Port(15~16)*1000M, SFP(S1~S2)*1000M
- ★ SFP Port: SFP(S1~S2)*1000M
- ★ Bandwidth: 36Gbps, MAC address: 8K
- ★ AI Watchdog: Automatic detection, Automatic restart
- ★ Support 4core 12+/36-Power Supply & Support 8 core 1245+/3678-power supply
- ★ Power: 300W
- ★ Transmission Distance: 130m
- ★ Operating Temperature: -30°C~60°C
- ★ Storage Temperature: -40°C~70°C
- ★ Size: 430*180*45mm (L*W*H)
- Model: GNT-P1018G6



24GE(PoE)+2SFP

- ★ Support IEEE802.3af/at/bt
- ★ 6KV lightning protection, 8KV Electro-Static, surge protection, anti-reverse connection, over-current protection, over-voltage protection, over-temperature protection, Short circuit protection
- ★ PoE Port: Port(1~24)*1000M
- ★ PoE++ Port: bt Port(23~24) 60W
- ★ UP-LINK: Port(23~24)*1000M, SFP(S1~S2)*1000M
- ★ SFP Port: SFP(S1~S2)*1000M
- ★ Bandwidth: 52Gbps, MAC address: 8K
- ★ AI Watchdog: Automatic detection, Automatic restart
- ★ Support 4core 12+/36-Power Supply & Support 8 core 1245+/3678-power supply
- ★ Power: 300W
- ★ Transmission Distance: 130m
- ★ Operating Temperature: -30°C~60°C
- ★ Storage Temperature: -40°C~70°C
- ★ Size: 430*180*45mm (L*W*H)
- Model: GNT-P1026G6