

ADVR8004A-NMH-V3

1 SATA.265 4ch Analog HD DVR A Series



Features:

- Support 4ch 5M-N unreal-time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 1080P output;
- Mini 1U Case, 1SATA(Up to 14TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G,WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control;
- Support coaxial audio;
- Support human detection, face detection Vehicle detection and other intelligence;

Model:

ADVR8004A-NMH-V3

Interface:



Parameters:

| | Model | ADVR8004A-NMH-V3 |
|------------|---------------|---|
| System | processor | NT98321 |
| Video | Codec | H.265/H.264 |
| | Preview | 4ch5M-N@20fps (6 in 1) / 4ch4M-N@30fps (6 in 1) / 4ch1080P (6 in 1) default5M-N |
| | Encode | 4ch5M-N@20fps (6 in 1) / 4ch4M-N@28fps (6 in 1) / 4ch1080P@25fps (6 in 1) default5M-N |
| | Decode | 2ch5M-N@20fps (6 in 1) / 2ch4M-N@28fps (6 in 1) / 2ch1080P@25fps (6 in 1) default5M-N |
| | Multi-mode | Analog:4ch 5M-N |
| | | hybrid: 4*5M-N (analog) + 2*1080P (network) |
| | Playback | IP: 16ch 1080P/8ch 5M |
| Audio | Coaxial audio | support |
| | Compression | G.711a |
| | Intercom | Support |
| Management | Record mode | Manual>Alarm>Motion detection>Timing |
| | Inquire mode | Inquire by Time/Calendar/Event/Channel |
| | Storage mode | HDD Storage, Network Storage |
| | Backup | Network, USB, SATA |
| Interface | Video input | 4*BNC (Support Coaxitron) |
| | HDMI output | 1*HDMI (MAX:1080P) |
| | VGA output | 1*VGA (MAX:1080P) |
| | Audio I/O | 1/1 |
| | Alarm I/O | 0/0 |
| | Ethernet port | 1*10/100Mbps Ethernet port, RJ45 port |
| | PTZ control | Support for multiple PTZ protocol |
| | USB Port | 2*USB2.0 ports |
| | HDD | 1*SATA interface (Up to 14TB) |
| General | Temperature | 0 °C - + 55 °C |
| | Humidity | 10% -90% RH |
| | Power supply | 12V/2A |
| | Consumption | <10W (Without HDD) |
| | Weight | Around1KG |
| | Dimension | 255mm(L)* 215mm(W)* 44mm(H) |



**click here to
watch now!**