

ADVR8016A-NGS-V4

1 SATA H.265 16ch Analog HD DVR A Series

Features:

- Support 16ch 4K unreal-time encoding;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output;
- Mini 1U Case, 1 SATA(Up to 14TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function;
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control;
- Support coaxial audio;
- Support intelligent analysis: Human detection, face detection, Vehicle shape detection;

Model:

ADVR8016A-NGS-V4

Interface:



Parameters:



	Model	ADVR8016A-NGS-V4
System	processor	NT98336
Video	Codec	H.265+/H.265/H.264
	Preview	16ch4K @7.5fps(6 in 1)/16ch5M@12.5fps(6 in 1)/16ch4M@15fps(6 in 1)/16ch3M@18fps(6 in 1)/16ch1080P(6 in 1)
	Encode	16ch4K @4fps(6 in 1)/16ch5M@6fps(6 in 1)/16ch4M@9fps(6 in 1)/16ch3M@10fps(6 in 1)/16ch1080P@16fps(6 in 1)
	Decode	4ch4K @4fps(6 in 1)/4ch5M@6fps(6 in 1)/4ch4M@9fps(6 in 1)/4ch3M@10fps(6 in 1)/4ch1080P@16fps(6 in 1)
	Multi-mode	Analog:16ch4K; 16ch5M;
		hybrid: 16ch4K (analog)+16ch4K (network)
	Playback	IP: 16ch4K; 16ch5M;
Audio	Coaxial audio	support
	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	16*BNC (Support Coaxitron)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	2*in/1*out
	Alarm I/O	0/0
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	1*SATA interface (Up to 14TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/2A
	Consumption	<10W (Without HDD)
	Weight	Around1KG
	Dimension	255mm(L)* 215mm(W)* 44mm(H)