

ADVR8016DA-GS

2 SATA.265 16ch AnalogHD DVR DA Series



Parameters :

	Model	ADVR8016DA-GS
System	Processor	Hi3531D
Video	Codec	H.265+/H.265/H.264
	Encode	16*5M@6fps;16*4M@8fps;16*4K-N@7fps
	Decode	4*5M@6fps;16*4M@8fps;4*4K-N@7fps
	Preview	16*5M@12fps;16*4M@15fps;16*4K-N@15fps
	Multi-mode	Analog:16*5M;16*4M(default); 16*4K-N (tick 16*5M mode) Hybrid:8*4M(analog)+8*4M (IP) 16*4M(analog)+16*4M (IP) IP:8*3M;4*5M
Audio	Compression	G.711a
	Intercom	Support
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	16*BNC(Support Coaxial)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	6/1
	Alarm I/O	4/1
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	3*USB2.0 ports
	HDD	2*SATA interface (Up to 8TB)
General	Temperature	0 °C - +55 °C
	Humidity	10%-90% RH
	Power supply	12V/4A
	Consumption	<10W (Without HDD)
	Weight	About 1.8KG
	Dimension	350mm(L)* 296mm(W)* 44mm(H)

Features :

- Support 16ch 4K-Nnon real-time recording;
- Support XVI,AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output
- 1U Case, 2 SATA(Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control

Model :

ADVR8016DA-GS

Interface :

